

VARIABLE VOLUME MICROPIPETTES

FEATURES

Constructed of high quality plastic and combined with stainless steel piston for many years of dependable service.

- Individually calibrated as per procedure laid down in ISO 8655 standards, a calibration report is provided with each pipette.
- Built-in, streamlined tip ejector facilitates easy tip ejection and access to narrow necked bottles and tubes.
- New body design provide improved ergonomics for more comfort and less fatigue during operation.
- User adjustment (re-calibration) can be performed easily.
- Easy volume adjustment by turning the plunger even when wearing gloves. Plunger does not snag gloves.
- Nine volume ranges cover the complete pipetting range from 0.2ul to 10ml offering a wide choice to select the most suitable model for any application.

Available in both Fully and Semi Autoclavable Versions.



Fully Autoclavable

Semi Autoclavable

Fully Autoclavable	Semi Autoclavable	Volume Range	Inc. μ l	Vol. μ l	Acc. $\pm\%$	CV $\leq\%$
FAA-2	VV-2	0.2-2.0 μ l	0.01	0.2	12.0	6.0
				1.0	2.5	1.5
				2.0	1.5	0.7
FAA-10	VV-10	0.5-10 μ l	0.1	0.5	5.0	2.8
				5.0	1.5	0.8
				10.0	1.0	0.4
FAA-20	VV-20	2-20 μ l	0.1	2.0	5.0	1.5
				10.0	1.0	0.6
				20.0	1.0	0.3
FAA-50	VV-50	5-50 μ l	1.0	5.0	2.5	1.5
				25.0	0.7	0.3
				50.0	0.7	0.3
FAA-100	VV-100	10-100 μ l	1.0	10.0	2.5	0.7
				50.0	0.8	0.3
				100.0	0.8	0.15
FAA-200	VV-200	20-200 μ l	1.0	20.0	2.5	0.7
				100.0	1.0	0.3
				200.0	0.6	0.2
FAA-1000	VV-1000	100-1000 μ l	10.0	100.0	1.6	0.3
				500.0	0.6	0.2
				1000.0	0.5	0.2
FAA-5000	VV-5000	0.5-5 ml	100.0	500.0	1.5	0.3
				2500.0	0.6	0.2
				5000.0	0.6	0.2
FAA-10000	VV-10000	1-10 ml	100.0	1000.0	1.5	0.3
				5000.0	0.6	0.2
				10000.0	0.6	0.2