



ALCOHOL BURNER, WICKLESS

A safe alternative to conventional alcohol burner, chrome plated tank has a screw top with rubber gasket. Uses a copper torch instead of a wick. capacity approx. 100 ml, fully leakproof.

CH10652



CENTRIFUGE, ECONOMICAL

Economical unit for small capacity centrifuging requirements. The standard unit is fitted with resiliently mounted motor with 3500 RPM for vibration free performance, a built in 5 step speed regulator and one non removable angle motor. complete with tube carriers. Available with following angle head rotors.

CH10654/1	15 ml x 4 tubes
CH10654/3	15 ml x 6 tubes
CH10654/5	15 ml x 8 tubes



CENTRIFUGE, UNIVERSAL

Compact model for routine work in laboratories. The special features include easy lid lock, stepless speed regulator and timer. Available with following rotors.

CH10655/1	15 ml x 4 tubes, 5000 RPM, Swing out head
CH10655/2	15 ml x 6 tubes, 5000 RPM, Swing out head
CH10655/3	15 ml x 8 tubes, 5000 RPM, Swing out head
CH10655/4	15 ml x 12 tubes, 4200 RPM, Angle head
CH10655/5	50 ml x 4 tubes, 2800 RPM, Angle head
CH10655/6	50 ml x 6 tubes, 2400 RPM, Angle head
CH10655/7	100 ml x 4 tubes, 2500 RPM, Angle head



1



2

CENTRIFUGE, MEDICO

For general purpose use in pathology labs, small hospitals, schools and colleges. The centrifuge with 5 step speed regulator is provided with swing out rotor head. Available in two models with 4 x 15 ml and 8 x 15 ml rotors.

Technical Data	CH10656/1 1	CH10656/3 2
Max. speed	3700 RPM	3500 RPM
Max. RCF	1950 xg	1900 xg
Max. tube size	15 ml	15 ml
Max. capacity	60 ml	120 ml
Connected load	0.11 kVA	0.13 kVA