

Measuring Cylinder, With Stoppers, Class B

- * Calibrated at 20°C
- * Complies with DIN ISO 4788 Standard
- * Graduations in Amber enamel

With Hex Base and PP stopper	With Hex Base and glass stopper	With Round Base and PP stopper	With Round Base and glass stopper	Capacity, ml	Tolerance, $\pm$ ml	Sub.-Div. ml	Pack Size
10.505.0005	10.507.0005	10.503.0005	10.506.0005	5	0.1	0.1	2
10.505.0010	10.507.0010	10.503.0010	10.506.0010	10	0.2	0.2	2
10.505.0025	10.507.0025	10.503.0025	10.506.0025	25	0.5	0.5	2
10.505.0050	10.507.0050	10.503.0050	10.506.0050	50	1	1	2
10.505.0100	10.507.0100	10.503.0100	10.506.0100	100	1	1	2
10.505.0250	10.507.0250	10.503.0250	10.506.0250	250	2	2	2
10.505.0500	10.507.0500	10.503.0500	10.506.0500	500	5	5	2
10.505.1000	10.507.1000	10.503.1000	10.506.1000	1000	10	10	1*
10.505.2000	10.507.2000	10.503.2000	10.506.2000	2000	20	20	1

Pack of 2 in case of round base



Nessler Cylinder

For color comparison.

- * Calibrated at 20°C
- * Facilitates colour comparison of water samples
- * Manufactured from precision bore 3.3 borosilicate tubing selected for freedom from colour or visible defects
- * White enamel inscriptions

	Capacity, ml	Sub.-Div. ml	Tolerance, $\pm$ ml	Pack Size
11.508.0050	50	25	0.4	2
11.508.0100	100	50	0.8	2



Dish Washer
Durable
Print

DIN ISO
4788