

Pipettes

www.supertekglassware.com

Supertek brand pipettes are manufactured from Low-expansion Boro 3.3 glass in conformance with ASTM E-438 TYPE 1 CLASS A glass and DIN ISO 3585, unless otherwise specified.

These pipettes are manufactured in accordance to DIN ISO 835 standard for Graduated pipettes and DIN ISO 648 standard for Volumetric pipettes.

All pipettes are screen printed in durable amber color which fuses into the glass. Each product is color coded to facilitate easy identification.

These Pipettes are made from specially selected accurate bore glass tubing, have precision formed jets, bevel ground ends to resist chipping. Mouth piece of pipettes is also tooled for easy sucking and cotton plugging.

Each Pipette Calibrated is to deliver (Ex, TD) at +20 °C reference temperature. The calibration also takes into account surface adhesion effects.

All A class pipettes have a waiting period of 5 seconds. Pipettes are available with conformity batch certificates and Individual certificate, which can be downloaded from www.supertekglassware.com Individual certificate is provided with the product. Batch certificate can also be provided with the product on request at extra cost.

Pipette Volumetric With One Mark, Bulb Type, Class A

- Calibrated at 20°C
- * Complies with ISO / DIN 648 Class A
- * Calibrated for delivery (TD, Ex)
- * Generally used for accurate measurement and decanting of liquid
- Markings are made in permanent amber stain diffused into the surface of the glass for better visibility and durability
- * Batch certificate is available on our website
- A calibration certificate is provided with each Individual certified product & same is available on our website

Batch	Individual	Capacity,	Tolerance,	Color Code	Pack size
Certificate	Certificate	ml	± ml		
11.301.0001	22.301.0001	1	800.0	Blue	10
11.301.0002	22.301.0002	2	0.01	Orange	10
11.301.0005	22.301.0005	5	0.015	White	5
11.301.0010	22.301.0010	10	0.02	Red	5
11.301.0020	22.301.0020	20	0.03	Yellow	5
11.301.0025	22.301.0025	25	0.03	Blue	5
11.301.0050	22.301.0050	50	0.05	Red	5
11.301.0100	22.301.0100	100	0.08	Yellow	2

Pipette Volumetric With One Mark, Bulb Type, Class B

- * Calibrated at 20°C
- * Complies with ISO / DIN 648 Class A
- * Calibrated for delivery (TD, Ex)
- * Generally used for accurate measurement and decanting of liquid
- * Markings are made in permanent amber stain diffused into the surface of the glass for better visibility and durability

	Capacity, ml	Tolerance, ± ml	Color Code	Pack size
10.301.0001	1	0.015	Blue	10
10.301.0002	2	0.02	Orange	10
10.301.0005	5	0.03	White	5
10.301.0010	10	0.04	Red	5
10.301.0020	20	0.06	Yellow	5
10.301.0025	25	0.06	Blue	5
10.301.0050	50	0.1	Red	5
10.301.0100	100	0.15	Yellow	2



