

DLAB LED Digital Rotary Evaporator is a basic chemical laboratory instrument suitable for evaporation, distillation and separation of chemicals. It can be used as a multifunctional system in combination with vacuum pump, vacuum controller and circulating refrigerators to provide excellent distillation solutions in many laboratory applications.

Features

- 5L heating bath with a wide temperature range (room temp.to180°C), independent temperature control, make it can be used separately. Water/oil heating mode can be changed only through a switch
- Manual lift combined with auxiliary lift for precise positioning of the glassware
- PID control ensures high temperature accuracy at $\pm 1^{\circ}\text{C}$ (water)
- Overheating protection temperature at 220°C
- Boil-dry protection, automatically power off if heating without water/oil in the heating bath
- Speed range from 20 to 200rpm, timing interval operation in clockwise and anticlockwise directions for drying process
- Patented condenser (cooling surface 1200/1700cm² for selection), double helix condensing tube + center circular arc design to speed up the flow rate of liquid with excellent cooling effect
- Ejection mechanism ensures easy exchange of evaporating flask
- Adjustable immersion angle
- Patented double spring sealing ring which is made of PTFE provides an excellent sealing performance
- Remote function provides PC control and data transmission
- Compatible with the entire range of RE100-Pro glassware
- Optional glassware with explosion proof film available



USB connector



Chemical resistance



Overheating protection



Compatible with all range of glassware

RE100-S LED Digital Rotary Evaporator



Specifications

Specifications		RE100-S
Motor Type		Brushless DC motor
Speed Range		20-200rpm
Display		LED (speed, temperature, time)
Clockwise and Anti-clockwise		Yes
Heating Temperature Range		Room temp. to 180°C
Control Accuracy		water: $\pm 1^{\circ}\text{C}$ oil: $\pm 3^{\circ}\text{C}$
Heating Power		1200 W
Stroke Displacement		Manual 110mm + auxiliary 100mm
Interval Time Setting Range		1~999s
Dimension [D×W×H]		Main Unit: 440×320×450mm Heating Bath: 300x300x240mm
Weight		Main Unit: 7kg Heating Bath: 3kg
Permissible Ambient Temperature		5~40°C
Permissible Relative Humidity		80%RH
Protection Class		IP20
USB Interface		Yes
Voltage/Frequency		100~120/200~240V 50/60 Hz
Power		1245 W