

### Flask Volumetric With Polypropylene Stopper, Class A

- \* Calibrated at 20°C
- \* Complies with ISO / DIN 1042 Class A
- \* Manufactured from 3.3 borosilicate glass for corrosion-free performance
- \* Amber enamel inscriptions
- \* [Batch certificate is available on our website](#)
- \* [A calibration certificate is provided with each Individual certified product & same is available on our website](#)

Batch Certificate	Individual Certificate	Capacity, ml	Tolerance, ± ml	Stopper Size	Pack size
11.402.0005	22.402.0005	5	0.025	10/19	6
11.402.0010	22.402.0010	10	0.025	10/19	6
11.402.0020	22.402.0020	20	0.04	10/19	2
11.402.0025	22.402.0025	25	0.04	10/19	2
11.402.0050	22.402.0050	50	0.06	12/21	2
11.402.0100	22.402.0100	100	0.1	14/23	2
11.402.0200	22.402.0200	200	0.15	14/23	2
11.402.0250	22.402.0250	250	0.15	14/23	2
11.402.0500	22.402.0500	500	0.25	19/26	2
11.402.1000	22.402.1000	1000	0.4	24/29	2
11.402.2000	22.402.2000	2000	0.6	29/32	1
11.402.5000	22.402.5000	5000	1.2	34/35	1



### Flask Volumetric, With Interchangeable Glass Stopper, Class A

- \* Calibrated at 20°C
- \* Complies with ISO / DIN 1042 Class A
- \* Manufactured from 3.3 borosilicate glass for corrosion-free performance
- \* Amber enamel inscriptions
- \* [Batch certificate is available on our website](#)
- \* [A calibration certificate is provided with each Individual certified product & same is available on our website](#)

Batch Certificate	Individual Certificate	Capacity, ml	Tolerance, ± ml	Stopper Size	Pack size
11.403.0005	22.403.0005	5	0.025	10/19	6
11.403.0010	22.403.0010	10	0.025	10/19	6
11.403.0020	22.403.0020	20	0.04	10/19	2
11.403.0025	22.403.0025	25	0.04	10/19	2
11.403.0050	22.403.0050	50	0.06	12/21	2
11.403.0100	22.403.0100	100	0.1	14/23	2
11.403.0200	22.403.0200	200	0.15	14/23	2
11.403.0250	22.403.0250	250	0.15	14/23	2
11.403.0500	22.403.0500	500	0.25	19/26	2
11.403.1000	22.403.1000	1000	0.4	24/29	2
11.403.2000	22.403.2000	2000	0.6	29/32	1
11.403.5000	22.403.5000	5000	1.2	34/35	1

ISO  
17025Dish Washer  
Durable  
PrintRetrace  
CodeDIN ISO  
1042